

SUPERTOP™-XL All-Surface Finish

For ALL Hard Surfaces plus STONELOK™-Sealed Floors & Countertops

longest-lasting with best possible protection

SUPERTOP™-XL is simply the best protection available for all hard surfaces such as VCT, wood, brick, terrazzo and concrete; and for StoneLok™-sealed floors and furniture. RJSC chemists have come up with breakthrough chemical technology that delivers all the benefits of earlier SuperTop formulations ... and then some.

With SuperTop-XL the surface is harder, more abrasion-resistant and more durable than with other finishes. The floor is also best protected from a wide range of contaminants such as oil, acetone, coffee, water and many beverage spills.

Application is easy and fast; and XL can be applied repetitively and seamlessly for an updated appearance in high-wear zones. With continuous SuperTop-XL coverage plus regular cleaning and wipe-up of spills, the life of a substrate can be extended virtually indefinitely.

PREPARE SURFACE by cleaning with RJSC StoneClean™ "60" or StoneClean "104" in a dilution appropriate to remove contamination and dust. Let dry.

APPLY using a new microfiber pad or short-shag roller.. Floor/substrate is ready for use in about 4 hours. For mirror finish, buff with sheepskin or other buffing pad 3 – 4 hours after application. Can also be burnished.

FOR POROUS SUBSTRATES, HIGH TRAFFIC SETTINGS; AND/OR TO GET SHINE OVER MATTE FINISHES OR DULL-LOOKING FLOORS, apply 2nd and/or 3rd coats. For StoneLok-sealed floors/furniture, apply when coating is print-free or after, but do not clean unless coating has cured for three (3) days.

COVERAGE RATE is about 600 - 1000 sq.ft./gallon, with additional coats typically at 800 – 1,200 sq.ft./gallon.

FOR PERIODIC RETOUCHING AS NEEDED, remove scuff marks/ground in dirt with white pad (or heavier if needed) on single action, lightweight, slow speed floor machine. Roll or mop SuperTop-XL onto prepared area. Let dry. Smooth out edges with soft buffer if needed.

FOR REGULAR CLEANING, use RJSC StoneClean "60" diluted 1:60 (about 2 ounces/gallon); or StoneClean "104" diluted 1:96 (4 oz. in 3 gallons). For stripping, use RJSC StoneClean & Strip with acetone or contact RJSC.

RICHARD JAMES
Specialty Chemicals Corp.

Visit www.rjsonline.com for information on our complete line of aqueous coatings, colorants and cleaners.

- ◆ **Beautiful high-gloss or mirror finish, XTRA low gloss (flat) or anti-skid**
- ◆ **Superior hardness and abrasion-resistance for extended durability**
- ◆ **Maximum protection in the class of renewable finishes**
- ◆ **For indoor and outdoor use with no yellowing or discoloration**
- ◆ **Easy touch-up of traffic patterns; no stripping required**

Specifications:

Solids 22%

VOC: ~25g/L

Gloss (typical) at 60°: Gloss 70; XTRA Low Gloss 15

See MSDS for complete health and safety data

Packaging:

Quarts and Cases of 4 quarts

Gallons and Cases of 6 gallons

5-Gallon Pails

Drums

Limited Warranty

The products of Richard James Specialty Chemicals Corporation (RJSC) contain highest quality raw materials and are manufactured under strict conditions of quality control. RJSC cleaners are warranted to conform to manufacturing specifications for a period of one year from initial delivery when stored in conditions greater than 32° F. and below 90° F. RJSC primers, sealers, Colloidal Dyes, primers and sealers with incorporated Colloidal Dyes, and floor finishes are warranted to conform to the manufacturing specifications for a period of six months from initial delivery when stored in conditions greater than 32° F and below 90° F. No warranty or affirmation of fact, express or implied, other than as set forth in this limited warranty is made by RJSC regarding its product(s). This limited warranty only applies to products purchased directly from RJSC. RJSC expressly disclaims all express and/or implied warranties for its product(s) that are not purchased directly from RJSC or are resold to or by third parties.

Due to the possibility of improper application, adverse surface or climactic conditions beyond our control, users of RJSC products shall make their own determinations, based on their own tests, as to the suitability of the product(s) for the intended purposes. RJSC hereby expressly disclaims any liability for claims that are due to product misuse, improper product selection, misapplication of product(s), substrate selection and preparation, environmental conditions and any failure to observe safety precautions. RJSC hereby disclaims any implied warranties of merchantability or fitness for any particular purpose regarding any product.

RJSC shall have no liability for consequential, incidental and/or special damages regarding the sale or use of a product even if the potential for such damages has been disclosed to Richard James Specialty Chemicals Corporation. RJSC's liability for product claims is limited to only replacement, at the option of RJSC or refund of the purchase price of the product applied per most current published directions. RJSC's liability shall not exceed the purchase price paid for the product and shall not include any special incidental or consequential losses or damages resulting from selection, use, installation, handling, care of or replacement of the product(s). The limited warranty does not include labor or the cost of labor for application.

Should a claim be asserted against RJSC by any party who did not purchase products directly from RJSC, RJSC shall be indemnified and held harmless by the party who did purchase the products directly from RJSC, including the reasonable attorneys' fees, costs and disbursements incurred by RJSC in its defense of any said claim. This indemnification shall not be deemed or in any manner expand or create a greater obligation on the part of RJSC than that set forth in this Limited Warranty

24 Ridge Street
Hastings-on-Hudson, NY 10706

(914) 478-7500 Fax: (914) 478-7516

www.rjsonline.com

SuperTop, StoneLok and StoneClean are trademarks of Richard James Specialty Chemicals Corp., Hastings on Hudson, NY 10706 © 1996 – 2017 (010517)