

## COATINGS APPLICATION TIPS: RJSC PRIMERS & SEALERS

*The tips that follow are designed to be used as ADDITIONAL TO the specific instructions provided for application of each product.*

### **StoneLok™ “MLT Plus,” StoneLok “10”, and TekSeal™ as primer coat -**

Should NOT be rolled onto smooth surfaces, only onto porous stone. HVLP is always best. For highest productivity, skilled applicators can use airless sprayer with FINEST TIP AVAILABLE, 100+ feet of hose to reduce pressure, and “you will need to run like hell”.

**TekSeal or TekSeal Dilute (TSD) for mottled color -** HVLP or pump-up sprayer with fine-adjustable nozzle to avoid pooling. Quick pull-and-release trigger motion achieves water-color-like effect. Often applied over water-misted surface. NEVER ALLOW WATER POOLING.

**100-Series™ for staining -** Pump-up sprayer with fine-adjustable-nozzle for mist to avoid pooling! Apply over water-misted surface

**200-Series™ over acid stain -** over dry substrate, airless sprayer, 6-15 or 6-17 tip, medium - heavy coat (about 4-5 mls), application as “wave” rather than straight across with overlap.

**200-Series as stain -** pump-up sprayer with fine-adjustable- nozzle to avoid pooling. Apply over water-misted surface.

**StoneLok “2K” & “E” caution -** “enhancement/darkening” can be significant. Therefore, be absolutely sure TekSeal or MLT Plus PRIMER has FULLY COVERED FLOOR (unless you want enhancement where substrate has no primer or color).

**StoneLok “2K” Gloss, Low Gloss or XTRA Low Gloss -** airless sprayer with 6-15 or 6-17 tip, 100+ feet of hose. “Dance” backwards with short width spray, 10”-12” off floor, and with 50% - 70% overlap. SEE SHEET ON COVERAGES! Pad or roller are acceptable in “V” with arc back roll.

**StoneLok “2K” Gloss-, Low Gloss-, and XTRA Low Gloss Anti Skid -** ANTI-SKID MUST BE CONSTANTLY STIRRED TO KEEP IN SOLUTION and TO MAINTAIN EVENNESS OF APPLICATION. Therefore, short-nap roller or paint pad are best. Airless sprayer with 6-19 tip is acceptable AS LONG AS POT CAN BE CONTINUOUSLY STIRRED.

**StoneLok “E” laydown -** This is self-leveler so you must get enough on the floor to allow this to happen. (SEE SHEET ON COVERAGES). Airless is best with 6-15 or 6-17 tip and 100+ feet of hose. “Dance” backwards with short width spray, 10” -12” off floor, and with 50% - 70% overlap. Pad or roller are acceptable in “V” pattern. Light back roll is recommended.

**Subject to RJSC Limited Warranty**